

## B.O.D. INCUBATOR ACE - 1

| Size                | Dimensions       |
|---------------------|------------------|
| 1.5 Cu. Ft (45 Ltr) | 35 x 35 x 35 Cm  |
| 3 Cu. Ft (90 Ltr)   | 45 x 45 x 50 Cm  |
| 6 Cu. Ft (180 Ltr)  | 51 x 51 x 71 Cm  |
| 10 Cu. Ft (300 Ltr) | 55 x 55 x 100 Cm |
| 12 Cu. Ft (360 Ltr) | 60 x 60 x 100 Cm |
| 16 Cu. Ft (480 Ltr) | 65 x 65 x 114 Cm |



- ➡ Designed Specially for Biological Oxygen Demand Determination and other applications like General incubation, Serum studies and enzyme assays tests.
- ➡ Double Walled Construction, Std & GMP Models.
- ➡ STD Model : Inner Chamber SS, Outer MS Powder Coated Body.
- ➡ GMP Model : Inner & Outer Chamber SS 304 Grade.
- ➡ Mounted on castor wheels for easy portability.
- ➡ Full length inner plexi glass /acrylic door for inspection of specimens without disturbing the temperature.
- ➡ Temperature controlled by Digital Temperature Controller cum indicator.  
Temperature range 5 Deg. C to 50 Deg. C with an accuracy of 0.5 Deg. C
- ➡ This unit is fitted with door operated illumination lamp inside the chamber.
- ➡ Equipped with hermetically sealed compressor.
- ➡ Air Circulation Fan for maintaining temperature uniformity through out the chamber.
- ➡ Flush fitting insulated double walled door has magnetic gasket.
- ➡ Provided with removable SS Shelves for complete flexibility in use.

Supplied by:  
ACE lab Equipment's